การลดผลิตภัณฑ์ของเสียในกระบวนการฉีดพลาสติก



นางสาวปวีณา วิทวัสกุล

วิทยานิพนธ์นี้เป็นส่วนหนึ่งของการศึกษาตามหลักสูตรปริญญาวิศวกรรมศาสตรมหาบัณฑิต สาขาวิชาการจัดการทางวิศวกรรม ศูนย์ระดับภูมิภาคทางวิศวกรรมระบบการผลิต คณะวิศวกรรมศาสตร์ จุฬาลงกรณ์มหาวิทยาลัย ปีการศึกษา 2546 ISBN 974-17-4310-6 ลิขสิทธ์ของจุฬาลงกรณ์มหาวิทยาลัย

DEFECTIVE PRODUCT REDUCTION FOR A PLASTIC INJECTION PROCESS

Miss Paveena Witthawaskul

A Thesis Submitted in Partial Fulfillment of the Requirements

for the Degree of Master of Engineering in Engineering Management

The Regional Centre for Manufacturing Systems Engineering

Faculty of Engineering

Chulalongkorn University

Academic Year 2003

ISBN 974-17-4310-6

Copyright of Chulalongkorn University

Ву	Miss Paveena Witthawaskul
Field of Study	Engineering Management
Thesis Advisor	Assistant Professor Prasert Akkharaprathomphong
Accept	ed by the Faculty of Engineering, Chulalongkorn University in Partial
Fulfillment of the Requi	rements for the Master 's Degree
	Dean of the Faculty of Engineering (Professor Somsak Panyakeow, D.Eng)
THESIS COMMITTEE	
	Binil Je Chairman
	(Professor Sirichan Thongprasert, Ph.D.)
	Saram Thesis Advisor
	(Assistant Professor Prasert Akkharaprathomphong, M.Eng)
	Member (Associate Professor Jeerapat Ngaoprasertwong)

Defective product reduction for a plastic injection process

Thesis Title

ปวีณา วิทวัสกุล: การลดผลิตภัณฑ์ของเสียในกระบวนการฉีดพลาสติก. (DEFECTIVE PRODUCT REDUCTION FOR A PLASTIC INJECTION PROCESS) อ.ที่ปรึกษา: ผู้ช่วยศาสตราจารย์ ประเสริฐ อัครประถมพงศ์, 69 หน้า. ISBN 974-17-4310-6.

วิทยานิพนธ์ฉบับนี้มีวัตถุประสงค์เพื่อลดผลิตภัณฑ์ของเสียในกระบวนการฉีดพลาสติก ของโรงงานตัวอย่างโดยใช้เครื่องมือทางคุณภาพในการศึกษา โดยในการศึกษาจะมุ่งเน้นไปที่ กระบวนการผลิตของผลิตภัณฑ์ตัวอย่างทั้ง 3 ขั้นตอน อันได้แก่ กระบวนการเกี่ยวกับวัตถุดิบ กระบวนการฉีดพลาสติก และกระบวนการตรวจสอบผลิตภัณฑ์ที่ผลิตได้

ในการศึกษาการลดผลิตภัณฑ์ของเสียในกระบวนการฉีดพลาสติกจะเริ่มจากการใช้ แผนภาพแสดงเหตุและผลมาพิจารณาปัจจัยที่มีผลกระทบต่อผลิตภัณฑ์ของเสียที่เกิดขึ้น จากนั้นจะ ใช้การวิเคราะห์ข้อบกพร่องและผลกระทบในกระบวนการมาใช้ในการวิเคราะห์ปัจจัยอีกครั้งเพื่อ หาค่าดัชนีความเสี่ยงชี้นำ จากนั้นแผนภาพความสัมพันธ์จะถูกนำมาใช้ในการแสดงความสัมพันธ์ ของปัจจัยต่างๆที่เกี่ยวข้องทั้งหมด ท้ายสุดการวิเคราะห์ด้วยคำถามทำไม ทำไม และแผนภาพการ ตัดสินใจต้นไม้จะถูกนำมาใช้เพื่อวิเคราะห์ถึงที่มาหรือต้นตอของปัญหา และหาวิธีแก้ปัญหาที่ เหมาะสมก่อนที่เราจะทำการปรับปรุงหรือแก้ไขปัญหาที่เกิดขึ้นต่อไป หลังจากที่ได้ทำการแก้ไข ปัญหาด้วยวิธีที่เหมาะสมแล้วนั้นจะพบว่าการลดผลิตภัณฑ์ของเสียหรือรอยคราบขาวที่เกิดขึ้น ประสบผลสำเร็จ โดยจากเดิมที่มีผลิตภัณฑ์ของเสียเท่ากับ 6.68% ในเดือนสิงหาคม 2546 กลับ ลคลงมาที่ 1.94% ในช่วงสัปดาห์ที่สองของเคือนตุลาคม หรือเท่ากับการลดการสูญเสียเป็นจำนวน เงิน 277.270 บาท ในช่วงระยะเวลา 6 สัปดาห์ โดยจากการศึกษาจะพบว่าทางเลือกที่เหมาะสมใน การลดผลิตภัณฑ์ของเสียมากที่สุดคือ ระบบการทำงานของชัทออฟวาล์ว ซึ่งค่าดัชนีความเสี่ยงชี้นำ หลังทำการปรับปรุงจะมีค่าลดลงมากกว่า 50%ของค่าก่อนทำการปรับปรุง อย่างไรก็ตามค่าดัชนี ความเสี่ยงชี้นำบางตัวไม่สามารถลดลงมาได้เนื่องจากปัจจัยภายนอกที่ไม่สามารถควบคุมได้ ข้อสังเกตที่ได้จากการทำวิจัยในครั้งนี้คือ ความร่วมมือจากบุคคลากรที่เกี่ยวข้องทุกฝ่ายนั้นเป็นสิ่ง สำคัญที่จะทำให้บรรลุถึงเป้าหมาย ถึงแม้ว่าจะมีการ โต้แย้งเกิดขึ้นบ้างเป็นครั้งคราว

ศูนย์ระดับภูมิภาคทางวิศวกรรมระบบการผลิต สาขาวิชาการจัดการทางวิศวกรรม ปีการศึกษา 2546 ##4571619821: MAJOR ENGINEERING MANAGEMENT KEY WORDS: CAUSE AND EFFECT DIAGRAMS / RELATION DIAGRAMS / CHECK SHEET / FAILURE MODE AND EFFECT ANALYSIS / PARETO DIAGRAMS / DECISION TREE DIAGRAMS / WHY-WHY ANALYSIS

PAVEENA WITTHAWASKUL: DEFECTIVE PRODUCT REDUCTION FOR A PLASTIC INJECTION PROCESS. THESIS ADVISOR: ASSISTANT PROFESSOR PRASERT AKKHARAPRATHOMPHONG. 69 pp. ISBN 974-17-4310-6

The objective of the thesis is to reduce the defective product for a plastic injection process in a sample company by using the quality improvement tools. This research focuses on the process of raw material, plastic injection, self inspection and process quality control, not including painting process and screening process.

Reduction of defective products for a plastic injection process starts from using cause and effect diagrams to explore all the potential influence factors affect on the defect product. Then, the Failure Mode and Effect Analysis is used to analyse the factors and shown the risk priority number. After that, the relation diagrams are used to illustrate the relation between each flaw. Finally, the Why-Why analysis and the decision tree diagrams are used to find the root cause of the highest risk priority number and find the solutions before we do the implementations.

After the proper implementations are applied, the defective products or silver streaks reduction are achieved. Those are the defective products reduced from 6.68% on August to 1.94% on the second week of October 2003, which equal to reduce 277,270 baht within six weeks. From the study, the best alternative to reduce the number of silver streaks defects is the mechanic-shut off valve system. In addition, the new risk priority number is lower than the former over 50%. However, some of the risk priority number cannot reduce because that is an uncontrollable factor. The observation on this research is the collaboration from every related person is an important thing to get the goal even though the controversies are happened sometimes.

The Regional Centre for Manufacturing Systems Engineering Field of study Engineering Management Academic year 2003

Student's signature Advisor's signature

Acknowledgements

I would like to express my deep gratitude to my thesis advisor, Assistant Professor Prasert Akkharaprathomphong, for his concern and valuable guidance during my research study. I would also like to thank to Professor Dr. Sirichan Thongprasert and Associate Professor Jeerapat Ngaoprasertwong for their kindly serving as chairman and member of the thesis examination committee and to their valuable comments and recommendations.

I would like to express my appreciation to all concern who encouraged and supported me in every way to undertake experiments with high satisfaction until this research has completed.

Eventually, I would like to express my greatest gratitude to my beloved parents and family for their understanding and encouragement as well as their deep concern throughout this academic programme.

Contents

Pages
Abstract (Thai)iv
Abstract (English)v
Acknowledgementsvi
Contentsvii
List of tablesix
List of figuresx
Chapter 1: Introduction
1.1 Background of research
1.2 Statement of problem 3
1.3 Objective of the study
1.4 Scope of the study
1.5 Research methodology4
1.6 Expected results4
Chapter 2: Theory and literature surveys5
2.1 Cause and effect diagrams5
2.2 Relation diagrams7
2.3 Check sheet 8
2.4 Failure Mode and Effect Analysis9
2.5 Pareto diagrams14
2.6 Decision tree diagrams16
2.7 Why-Why analysis17
2.8 Literature surveys17
Chapter 3: Plastic injection products and processes19
3.1 Plastic injection products19
3.2 Overall production process
3.3 Raw material
3.4 Injection process
3.5 Self inspection and process quality control25
Chapter 4: Data collection and analysis26
4.1 Data collection
4.2 Cause and effect diagram26
4.3 Failure Mode and Effect Analysis (FMEA)31
4.4 Relation diagrams36
4.5 Why-Why analysis and decision tree diagrams38

Contents (continued)

	Pages
Chapter 5: Implementation	48
5.1 Mould design	48
5.2 Shut off valve system	
5.3 Continual maintenance	
5.4 The delayed time of gas injection	
5.5 Raw material receiving	
Chapter 6: Conclusion and recommendations	61
6.1 Conclusion	61
6.2 Alternative suggestion	
6.3 Limitation of the study	64
6.4 Recommendations	
References	66
Biography	
Diography	

List of tables

	Pages
Table 4.1: Data collection of silver streaks defect on	26
selected product from March to August 2003	
Table 4.2: FMEA of silver streaks defect	32
Table 4.3: FMEA of silver streaks defect and recommended action	45
Table 5.1: Switching sampling plan of raw material receiving	57
Table 5.2: FMEA of silver streaks defect and new RPN number	58
Table 6.1: Data collection of silver streaks defect on selected	63
product from March to the first two weeks of October 2003	

List of figures

Figure	Pages
Figure 1.1: Company's organization	2
Figure 1.2: The defective parts per million of	3
front cabinet of television 14 inches	
Figure 2.1: Causes and effect diagram	7
Figure 2.2: Relation diagrams	8
Figure 2.3: Check sheet	9
Figure 2.4: Step of FMEA implementation	14
Figure 2.5: Pareto diagram	
Figure 3.1: Plastic products	19
Figure 3.2: Research's product	19
Figure 3.3: Company's product	
Figure 3.4: Plastic injection process	
Figure 3.5: Raw material	
Figure 3.6: Hopper machine	
Figure 3.7: Injection process machine	
Figure 4.1: Silver streaks defect	
Figure 4.2: Cause and effect diagram of silver streaks defect	
Figure 4.3: Pareto diagram of silver streak defect	
Figure 4.4: Relation diagrams of silver streaks	
Figure 4.5: Why-Why analysis of silver streaks	
Figure 4.6: Decision tree diagrams of silver streaks	41
Figure 4.7: The shut off valve out of order	
Figure 5.1: Silver streaks in September 2003 by	50
using new shut off valve system	5 4
Figure 5.2: Actual temperature of heater no. 1 in September 2003	
Figure 5.3: Actual temperature of heater no. 2 in September 2003	51
Figure 5.4: Actual temperature of heater no. 3 in September 2003	52
Figure 5.5: Actual temperature of heater no. 4 in September 2003	
Figure 5.6: Actual temperature of heater no. 5 in September 2003	
Figure 5.7: Actual temperature of heater no. 6 in September 2003	
Figure 5.8: Silver streaks in September 2003 with	54
the heaters ready in use	
Figure 5.9: Silver streaks in October 2003 by	55
using a full option machine	F.0
Figure 5.10: Raw material check sheet	56
Figure 6.1: The RPN number between before and	62
after implementation	