

REFERENCES

- A.D. Chirico, M. Armanini, P. Chini, and G. Cioccolo. Polym. Deg. and Stab., **79**, 139 (2003).
- A.D.L. Rosa, A. Recca, J.T. Carter, and P.T. McGrail. Polymer, **40**, 4093 (1999).
- A.H. Landrock. Handbook of Plastics Flammability and Combustion Toxicology, NOYES PUBLICATIONS, New Jersey (1983).
- A.K Bledzki and J. Gassan. Prog. Polym. Sci. **24**, 221 (1999).
- B. Li and J. He. Polym. Deg. and Stab. **83**, 241 (2004).
- C.A. Harper. Handbook of Building Materials for Fire Protection. New York : McGRAW-HILL, (2004).
- C.B. Vick, Adhesive Bonding of Wood Materials, Wood Handbook, Madison (1999).
- C.C.M. Ma, H.D. Wu, Y.F. Su, M.S. Lee, and Y.D. Wu. Composites., **28**, 895 (1997a).
- C.P.R. Nair. Prog. Polym. Sci. (2004).
- D.A. Johnson, D.A Johnson, J.L. Urich, and M. Krainbill. Proceedings of the 1999 Ag fiber technology, Agro Plastics (1999).
- D.N. Saheb and J.P. Jog. Advance in Polymer Technology **18**, 351 (1999).
- E.A. Turi. Thermal Characterization of Polymeric Materials. San Diego : Academic Press, (1981).
- E. Jakab, G. Varhegyi, and O. Faix. J. Anal. Appl. Pyrolysis, **56**, 273 (2000).
- G.L. Nelson. ACS Symposium Series 797 (1995).
- H. Ishida, and D.J. Allen. J. Polym. Sci. Phys., **34**, 001 (1996b).
- H. Ishida, U.S. Patent 5,543,516 (1996).
- H.T. Chiu, S.H. Chiu, R.E. Jeng, and J.S. Chung. Polym. Deg. and Stab. **70**, 505 (2000).
- H. Zhang, P.R. Westmoreland, R.J. Farris, E.B. Coughlin, A. Plichta, and Z.K. Brzozowski. Polymer, **43**, 5463 (2002).
- J.A. Youngquist. Wood-based Composites and Panel Products. Wood Handbook. Madison (1999).
- J. Jang, H. Chung, M. Kim, and H. Sung. Polym. Testings., **19**, 269 (2000).
- J. L. Odell. The Fourth International Conference on Woodfiber-Plastic Composites. Madison.
- J.W. Lyons. Flame Retardants, Encyclopedia of chemical technology. **10**, 348 (1991).
- K. Sandler, Polymer Synthesis Volume II. New York : Academic Press, (1994).
- M. Sain, S.H. Park, F. Suhara, and S. Law. Polym. Deg. and Stab. **83**, 363 (2004).
- M. Sohoni. Phenolic resins, Polymer Data Handbook, New York: Oxford University Press, (1999).
- N.E. Marcovich, M.I. Aranguren, and M.M. Reboredo. Polymer **42**, 815 (2001).
- N.E. Marcovich, M.M. Reboredo, and M.I. Aranguren. Thermochim. Acta, **372**, 45 (2001).
- N. Jalongwongsha. Effect of types and amount of phenolic resins on curing reaction, thermal properties and ignition behavior of polymer alloy benzoxazine/phenolic. Master's degree, Department of Material Science, Faculty of Science, Chulalongkorn University, 2003.
- P.A. Staniland. Molecular Design of High-Temperature Polymers, Wilton.

- P.S Achary and R Ramaswamy. *J. Appl. Polym. Sci.*, **69**, 1187 (1998).
- P.W. Balasuriya, L. Ye, and Y.W. Mai. *Composites* **32**, 619(2001).
- R. Antony and C.K.S. Pillai. *J. Appl. Polym. Sci.* **54**, 429 (1994).
- R.B. Miller. *Structure of Wood, Wood Handbook*, Madison (1999).
- S. Mishra, J.B. Naik, and Y.P. Patil. *Advances in Polymer Technology*. **23**, 46 (2004).
- S. Pirstprindwong. *The flexibility enhancement of polybenzoxazine using flexible epoxy and urethane prepolymer*. Master's degree, Department of Chemical Engineering, Faculty of Engineering, Chulalongkorn University, 2003.
- S. Rimdusit and H. Ishida. *Polymer* **41**, 7941 (2000).
- S. Rimdusit and H. Ishida. *J. Polym. Sci. Phys.* **38**, 1687 (2000b).
- S. Rimdusit and H. Ishida. *Rheologica Acta* **38**, 1687 (2000b).
- S.I. Farid, M.T. Kortschot, and J.K. Spelt. *Polym. Eng. Sci.* **42**, 2336 (2002).
- S.N. Ghosh and S. Maiti. *Eur. Polym. J.* **34**, 849 (1998).
- T. Takeichi, R. Zeidam, and T. Agag. *Polyme.* **43**, 45 (2002).
- T. Yamagishi, M. Enoki, M. Inui, H. Furukawa, Y. Nakamoto, and S. Ishida. *J. Polym. Sci. Chem.* **31**, 675 (1993a).
- www.UN/SCETDG/19/INF.43
- www.uwsp.edu/papersci/biasca/ps350/physical%20Properties.htm
- W. Simpson and A. Tenwolde, *Physical Properties and Moisture Relations of Wood, Wood Handbook*, Madison (1999).
- X. Ning, and H. Ishida. *J. Polym. Sci. Chem.* **32**, 1121 (1994a).
- Y.L. Liu, C.S. Wu, K.Y. Hsu, and T.C. Chang. *J. Polym. Sci.*, **40**, 2329 (2002).

ศูนย์วิทยทรัพยากร
จุฬาลงกรณ์มหาวิทยาลัย



APPENDICES

ศูนย์วิทยทรัพยากร
จุฬาลงกรณ์มหาวิทยาลัย

APPENDIX A

Characterization of Benzoxazine/Phenolic Novolac Alloys

Appendix A-1 Limiting oxygen index of BP alloys.

Phenolic Novolac Mass Fraction	Limiting Oxygen Index, LOI
0.0	30.1
0.1	30.7
0.2	30.8
0.3	31.0

Appendix A-2 Heat of combustion of BP alloys.

Phenolic Novolac Mass Fraction	Heat of Combustion, HOC (kJ/g)
0.0	34.95
0.1	34.43
0.2	34.30
0.3	33.82

Appendix A-3 Char yield of BP alloys.

Phenolic Novolac Mass Fraction	Char Yield (%)
0.0	25.05
0.1	34.28
0.2	36.27
0.3	36.89
0.5	38.47
0.7	37.48

Appendix A-4 Degradation temperature of BP alloys.

Phenolic Novolac Mass Fraction	Degradation Temperature, T_d ($^{\circ}\text{C}$)	
	5% weight loss	10% weight loss
0.0	334.17	355.04
0.1	353.46	368.25
0.2	349.81	374.44
0.3	345.87	371.65
0.5	326.39	356.57
0.7	307.55	341.04

Appendix A-5 Glass transition temperature of BP alloys.

Phenolic Novolac Mass Fraction	Glass-transition Temperature, T_g ($^{\circ}\text{C}$)
0.0	165.93
0.1	159.12
0.2	145.00
0.3	138.86
0.5	111.55

ศูนย์วิทยทรัพยากร
จุฬาลงกรณ์มหาวิทยาลัย

APPENDIX B

Flammability Characterization of Woodflour-filled Benzoxazine/Phenolic Novolac Alloys

Appendix B-1 Limiting oxygen index of woodflour-filled BP alloys with 50%, 60%, and 70% by weight of woodflour content.

Phenolic Novolac Mass Fraction	Limiting Oxygen Index, LOI		
	50% by weight WF	60% by weight WF	70% by weight WF
0.0	25.2 ± 0.2	23.2 ± 0.1	22.8 ± 0.0
0.1	25.6 ± 0.4	23.6 ± 0.1	23.0 ± 0.1
0.2	25.5 ± 0.1	23.7 ± 0.1	23.3 ± 0.1
0.3	26.2 ± 0.1	23.9 ± 0.1	23.4 ± 0.1
0.5	27.1 ± 0.1	24.5 ± 0.1	23.7 ± 0.2
0.7	28.1 ± 0.1	26.2 ± 0.1	24.4 ± 0.1

Appendix B-2 Rate of burning of woodflour-filled BP alloys with 50% and 70% by weight of woodflour content.

Phenolic Novolac Mass Fraction	Rate of Burning (mm/min)	
	50% by weight WF	70% by weight WF
0.0	17.65 ± 0.4	18.06 ± 0.5
0.1	16.39 ± 0.8	17.38 ± 0.9
0.2	no burning rate	16.58 ± 0.7
0.3	no burning rate	16.16 ± 0.2
0.5	no burning rate	14.97 ± 1.2

Appendix B-3 Heat of combustion of woodflour-filled BP82.

Woodflour Content (%)	Heat of Combustion, HOC (kJ/g)
0	34.3
50	26.3
70	23.1
100	19.4



ศูนย์วิทยทรัพยากร
จุฬาลงกรณ์มหาวิทยาลัย

APPENDIX C

Thermal Characterization of Woodflour-filled Benzoxazine/Phenolic Novolac Alloys

Appendix C-1 Degradation temperature of woodflour-filled BP alloys.

Phenolic Novolac Mass Fraction	Degradation Temperature, T_d (°C)			
	50% by weight WF- 5% weight loss	50% by weight WF- 10% weight loss	70% by weight WF- 5% weight loss	70% by weight WF- 10% weight loss
0.0	279.66	304.71	271.19	289.55
0.1	287.81	310.63	275.43	294.69
0.2	289.66	312.86	274.64	295.88
0.3	290.21	312.57	276.92	297.88
0.5	289.99	313.09	279.48	298.61
0.7	285.64	313.39	270.17	293.92

Appendix C-2 Char yield of woodflour-filled BP alloys at 850°C with 50% and 70% by weight of woodflour content.

Phenolic Novolac Mass Fraction	Char Yield (%)	
	50% by weight WF	70% by weight WF
0.0	35.909	32.415
0.1	36.810	34.518
0.2	39.846	35.105
0.3	39.460	36.018
0.5	39.771	36.163
0.7	38.178	34.401

APPENDIX D

Mechanical Characterization of Woodflour-filled Benzoxazine/Phenolic Novolac Alloys

Appendix D-1 Flexural properties of woodflour-filled BP alloys.

Phenolic Novolac Mass Fraction	Flexural Modulus (GPa)		Flexural Strength (MPa)	
	50% by weight WF	70% by weight WF	50% by weight WF	70% by weight WF
0.0	5.8	6.1	60.3	59.3
0.1	5.7	6.1	61.3	58.5
0.2	6.4	6.4	64.5	57.8
0.3	5.3	6.0	65.6	62
0.5	5.5	6.1	65	69

Appendix D-2 Glass transition temperature of woodflour-filled BP alloys at 70% by weight of woodflour content.

Phenolic Novolac Mass Fraction	Glass-transition Temperature, T_g ($^{\circ}\text{C}$)
0.0	200
0.1	215
0.2	205

APPENDIX E

Physical Characterization of Woodflour-filled Benzoxazine/Phenolic Novolac Alloys

Appendix E-1 Density of woodflour-filled BP alloys at 50% by weight and 70% by weight of woodflour.

Wood Content	Phenolic Novolac Mass Fraction	Actual Density (g/cm ³)	Theoretical Density (g/cm ³)
50% by weight	0.0	1.32	1.33
	0.1	1.32	1.33
	0.2	1.32	1.34
	0.3	1.32	1.34
	0.5	1.33	1.35
	0.7	1.34	1.36
70% by weight	0.0	1.38	1.39
	0.1	1.37	1.39
	0.2	1.38	1.40
	0.3	1.36	1.40
	0.5	1.36	1.40
	0.7	1.37	1.41

Appendix E-2 Water absorption of woodflour-filled BP82 with 70% by weight of woodflour content.

Time	Water Absorption (%)
24 hours	3.11
7 days	10.20
saturation	16.12

VITA

Ms. Natcha Kampangsaeree was born in Bangkok, Thailand on August 10, 1980. She graduated at high school level in 1998 from Satreewatabsorn sawan School. She received the Bachelor's Degree of Engineering with a major in Chemical Engineering from the Faculty of Engineering, King Mongkut's University of Technology Thonburi in 2002. After graduation, she entered study for a Master's Degree of Chemical Engineering at the Department of Chemical Engineering, Faculty of Engineering, Chulalongkorn University.

