

การเคลื่อนตัวของคินเนื่องจากการจากขุดเจาะอุโมงค์ด้วยหัวเจาะแรงดันคินสมดูลในดินกรุงเทพฯ

นายชกไทดิม

วิทยานิพนธ์นี้เป็นส่วนหนึ่งของการศึกษาตามหลักสูตรปริญญาวิศวกรรมศาสตรดุษฎีบัณฑิต  
ภาควิชาวิศวกรรมโยธา  
คณะวิศวกรรมศาสตร์ จุฬาลงกรณ์มหาวิทยาลัย  
ปีการศึกษา 2549  
ลิขสิทธิ์ของจุฬาลงกรณ์มหาวิทยาลัย

491204

Thesis Title                    GROUND MOVEMENT RESPONSE DUE TO EARTH  
                                  PRESSURE BALANCE SHIELD TUNNELING IN  
                                  BANGKOK SUBSOIL

By                            Soktay Lim


Field of Study               Civil Engineering

Thesis Advisor              Associate Professor Wanchai Teparaksa, D. Eng.


Thesis Co-advisor           Professor Satoru Shibuya, Ph.D.


---


Accepted by the Faculty of Engineering, Chulalongkorn University in  
Partial Fulfillment of the Requirements for the Doctoral Degree


 ..... Dean of the Faculty of Engineering  
(Professor Direk Lavansiri, Ph.D.)

THESIS COMMITTEE

 ..... Chairman  
(Associate Professor Boonsom Lerdirunwong, D. Ing.)

 ..... Thesis Advisor  
(Associate Professor Wanchai Teparaksa, D. Eng.)

 ..... Thesis Co-advisor  
(Professor Satoru Shibuya, Ph.D.)

 ..... Member  
(Assistant Professor Tirawat Boonyatee, D. Eng.)

 ..... Member  
(Tanate Srisirirojanakorn, Ph.D.)

 ..... Member  
(Attasit Sawatparnich, Ph.D.)


นายชกไก่ ลิม: การเคลื่อนตัวของดินเนื่องจากการจากบุคเจาะอุ่โนงค์ด้วยหัวเจาะแรงดันดินสมดุล  
ในดินกรุงเทพฯ (GROUND MOVEMENT RESPONSE DUE TO EARTH  
PRESSURE BALANCE SHIELD TUNNELING IN BANGKOK SUBSOIL) อ.  
ที่ปรึกษา: รศ. ดร. วันชัย เทพรักษ์, อ.ที่ปรึกษาร่วม: PROF. SATORU SHIBUYA,  
Ph.D. 176 หน้า.

พฤติกรรมการทรุดตัวของดินยังคงเป็นคำาณโดยเฉลี่ยอย่างยิ่งสำหรับการบุคเจาะอุ่โนงค์ใน  
พื้นที่เขตเมืองที่มีประชากรอาศัยหนาแน่นและมีอุปสรรคสิ่งกีดขวางมากมายตลอดแนวการบุคเจาะ  
อุ่โนงค์ งานวิจัยนี้ทำการศึกษาพฤติกรรมการทรุดตัวของดินเนื่องจากการบุคเจาะอุ่โนงค์และทำการ  
วิเคราะห์กลับด้วยวิธีไฟฟ้าในท่อสื่อสาร สองมิติเพื่อการประมาณค่าการทรุดตัวอย่างเหมาะสมในการบุค  
เจาะอุ่โนงค์ในกรุงเทพฯ

อุ่โนงค์ระบายน้ำขนาดเส้นผ่านศูนย์กลางภายนอก 5.55 ม. ในโครงการคลองระบายน้ำแสน  
แสบ-คลองลาดพร้าว-สถานีสูบน้ำพระโขนง ได้ทำการบุคเจาะด้วยหัวเจาะแรงดันดินสมดุลทึ้งการบุคเจาะ  
อุ่โนงค์ในชั้นรายແน่นและดินเหนียวแข็งดินดานที่ความลึกศูนย์กลางอุ่โนงค์ประมาณ 27.50 ม. ต่ำจาก  
ผิวดิน ผลการตรวจวัดการเคลื่อนตัวของดินจากการบุคเจาะอุ่โนงค์สามารถแบ่งได้เป็น 3 ส่วนคือ การทรุด  
ตัวก่อนถึงหัวเจาะ การทรุดตัวในหัวเจาะ และการทรุดตัวของช่องว่างระหว่างอุ่โนงค์กับดินภายหลังการ  
เจาะผ่านของหัวเจาะ (Tail Void) การทรุดตัวที่ผิวดินหลักๆ เกิดขึ้นจากช่องว่างระหว่างอุ่โนงค์กับดิน  
ภายหลังการเจาะผ่านของหัวเจาะประมาณ 63-67 % ของการทรุดตัวทึ้งหมด สำหรับการบุคเจาะอุ่โนงค์  
ระบายน้ำทึ้งในชั้นรายແน่นและชั้นดินเหนียวแข็งดินดาน

การวิเคราะห์การทรุดตัวของดินได้ทำการวิเคราะห์ด้วยวิธีไฟฟ้าในท่อสื่อสารโดยอ้างอิงพฤติกรรม  
การพังทลายของดินชนิด Mohr-Coulomb เพื่อยืนยันผลการตรวจวัดการทรุดตัวที่ผิวดินทึ้งกรณีการบุค  
เจาะอุ่โนงค์ปกติ การบุคเจาะอุ่โนงค์ผ่านได้ฐานรากเสาเข็มสะพานคลองดัน และบุคเจาะอุ่โนงค์ผ่าน  
ด้านข้างฐานรากเสาเข็มตอนม่อรอดไฟฟ้า BTS อัตราส่วนระหว่าง Young Modulus กับกำลังรับแรง  
เฉื่อนของดิน ( $E_u/S_u$ ) จากการวิเคราะห์กลับด้วยวิธีไฟฟ้าในท่อสื่อสาร พนวณค่าประมาณ 240, 360 และ  
480 สำหรับดินเหนียวอ่อน ดินเหนียวแข็งปานกลาง และดินเหนียวแข็งมากตามลำดับ ในขณะที่ ค่า  
Drain Modulus ( $E'$ ,  $\text{kN}/\text{m}^2$ ) ในชั้นรายແน่นมีค่าประมาณ  $2000 N_{60}$  ผลการประเมินการทรุดตัวที่  
ผิวดินด้วยวิธี Empirical พนวณค่าของเบต้าความกว้างของการทรุดตัว ( $i$ ) มีค่าประมาณ  $0.24z_0 - 0.35z_0$  สำหรับการบุคเจาะอุ่โนงค์ในชั้นรายແน่น และเพิ่มกว้างขึ้นเป็นประมาณ  $0.46z_0$  สำหรับการบุค  
เจาะอุ่โนงค์ในชั้นดินเหนียวแข็งดินดาน

ภาควิชา..... วิศวกรรมโยธา.....  
สาขาวิชา..... วิศวกรรมโยธา.....  
ปีการศึกษา ..... 2549 .....

ลายมือชื่อนิสิต.....   
ลายมือชื่ออาจารย์ที่ปรึกษา.....   
ลายมือชื่ออาจารย์ที่ปรึกษาร่วม..... 

# # 4671844721: MAJOR CIVIL ENGINEERING

KEY WORD: EPB SHIELD TUNNELING/ GROUND LOSS/ GROUND MOVEMENTS/ OBSTRUCTIONS/ FE BACK SIMULATION

SOKTAY LIM: GROUND MOVEMENT RESPONSE DUE TO EARTH PRESSURE BALANCE SHIELD TUNNELING IN BANGKOK SUBSOIL.  
THESIS ADVISOR: ASSOC. PROF. WANCHAI TEPARAKSA, D. Eng.,  
THESIS CO-ADVISOR: PROF. SATORU SHIBUYA, Ph.D., 176 pp.

Ground surface and subsurface movement behaviors remained the questions, especially for the tunnels bored in the densely populated urban area where the several obstructions are usually found along the tunneling route. This research aims to study the behavior of ground surface and subsurface deformations due to tunneling and to do the back analysis based on the 2D FE analysis for an appropriate settlement prediction of tunnel in Bangkok.

An OD 5.55 m flood diversion tunnel of Saensaep-Latphrao Phrakanong project was bored by means of EPB shield machine in both dense silty sand and hard silty clay layers with centerline at about 27.50 m below ground surface. Half route of the tunnel was bored underneath two bridges and busy roads. The recorded ground surface and subsurface response can be classified into 3 phases as deformation in front of the shield face, deformation within the shield body and deformation due to tail void behind the shield. The major ground surface settlement induced by tail void is about 63-67% of total ground surface settlement for tunneling in both dense silty sand and hard silty clay layers. The 2D FE analysis was carried out based on Elasto-Plastic (Mohr-Coulomb) failure criteria to confirm with ground settlements monitored at different cases of tunneling: tunnel bored without obstructions, under the Klongtan bridge pile foundation and adjacent to the BTS sky train pile foundation. The ratio  $E_u/S_u$  for FE analysis has been confirmed as 240, 360 and 480 for soft clay, medium stiff clay and stiff silty clay layers, respectively. In addition,  $E'(kN/m^2) = 2000.N_{60}$  can be used for dense silty sand layers. The surface settlement trough width,  $i$ , based on empirical method is found between  $0.24z_0$  and  $0.35z_0$  for tunnel excavated in dense silty layer and it is increased to  $0.46z_0$ , which is wider, for tunnel in hard silty clay.

Department.....	Civil Engineering.....	Student's signature.....
Field of study.....	Civil Engineering.....	Advisor's signature.....
Academic year.....	2006.....	Co-advisor's signature.....

## ACKNOWLEDGEMENT

Many people have supported me in different ways during my doctoral program at both Chulalongkorn University and Kobe University. Without their helps and supports, this work is not possible.

I would like to thank JICA and AUN/Seed-Net for their financial support without their funding the starting point cannot happen.

I deeply appreciate the enormous academic support from three professors: Associate Professor Dr. Wanchai TEPARAKSA, major advisor, for his advice on this work and for provision on necessary documents; Professor Dr. Satoru SHIBUYA, co-advisor, for his encouragement and invaluable advice not only during my research in geotechnical laboratory at Kobe University, but also during my works at Chulalongkorn University; Assistant professor Dr. Tirawat BOONYATEE, committee member, for his encouragement and revision of some parts related to the review of Finite Element Method.

This field data collection won't be possible without cooperation and involvement of the following personnel of a joint venture of Italian-Thai Development PCL and Nishimatsu Construction Co., Ltd. in Bangkok: Mr. Kobchai PORNPRASIT and Mr. Sumate SANGMANEE, site engineers.

I am grateful to Assistant Professor Dr. Sangrawee CHAOPRICHCHA, Technical writing professor for being my editor.

In addition, the author likes to express his cordial thanks to all the thesis committee members for their invaluable comments during the thesis proposal defense.

A further word of thanks is devoted to all the former master students of Geotechnical Engineering Division, Chulalongkorn University, and the PhD students under supervision of Associate Professor Dr. Wanchai TEPARAKSA for their support on FEM analysis and the research activities.

Finally, very special gratitude goes to my family in Cambodia, my parents, brother and sisters, and especially my wife, Sodany TANN and my daughter Seavmey LIM for their mental support, continuous encouragement, and patience.

# CONTENTS

	Page
Abstract in Thai.....	iv
Abstract in English.....	v
Acknowledgement .....	vi
Contents .....	vii
List of Tables .....	xi
List of Figures.....	xii
List of Symbols.....	xviii
Chapter I.....	1
Introduction.....	1
1.1 Motivation and Background .....	1
1.2 Statement of the Problem.....	3
1.3 Research Objectives.....	3
1.4 Research Scope .....	4
1.5 Strength of the Study .....	4
1.6 Layout of the Thesis.....	5
Chapter II .....	6
TBM and Tunneling Method .....	6
2.1 History of Shield Tunneling Methods.....	6
2.2 Different Kinds of TBMs.....	8
2.2.1 Rock TBMs.....	8
2.2.2 Soft Ground TBMs .....	10
2.2.3 Slurry Shield Machine .....	11
2.2.4. EPB Shield Machine .....	12
2.3 Criteria for Selection of Soft Ground TBMs .....	13
2.4 EPB Tunneling Method .....	17
2.4.1 History of EPB Shield Machine: its development and implementation .....	17
2.4.2 Tunnel Excavation .....	20
2.4.3 Erection of Segmental Lining .....	22

2.4.4 Grouting of Tail Void .....	24
Chapter III.....	26
Geology and Subsoil Conditions .....	26
3.1 Geology of Bangkok Soil.....	26
3.2 Underground Water of Bangkok.....	28
3.3 Subsoil Conditions along the Tunneling Route of the Project.....	29
Chapter IV.....	32
Tunnel Induced Ground Movements .....	32
4.1 Causes of Soil Displacements around Tunnels in Soft Soil.....	32
4.1.1 Displacement Vectors in Soft Soils.....	32
4.1.2 Causes of Soil Displacements.....	33
4.2 Predicting Methods of Ground Displacements .....	38
4.2.1 Empirical Methods.....	40
4.2.2 Analytical Methods.....	48
4.2.3 Laboratory Testing.....	53
4.2.4 Numerical Analysis Methods.....	55
4.3 Appropriate Methods for Analyses of the Research Project.....	58
Chapter V .....	59
Project Description and Monitoring System.....	59
5.1 General Description .....	59
5.2 Soil Profiles of Selected Analysis Sections .....	63
5.3 TBM Used in the Project .....	65
5.4 Tunnel Properties .....	67
5.5 Monitoring System.....	68
5.5.1 Inclinometers.....	69
5.5.2 Extensometers .....	71
5.5.3 Total Earth Pressure Cells.....	74
5.5.4 Convergence Bolts .....	75
5.6 Layouts of Instrumentation at the Sites of the Study .....	76
Chapter VI.....	78
Numerical Method and Analyses.....	78
6.1 Sign Conventions and Units.....	79
6.1.1 Sign Conventions .....	79
6.1.2 Units.....	79

6.2 Geometric Input .....	80
6.3 Mesh Generation.....	80
6.4 Elements and Accuracy of Calculation.....	81
6.5 Structural Elements.....	82
6.6 Interfaces.....	83
6.7 Soil Models .....	83
6.8 Automatic Load Stepping .....	85
6.9 Staged Construction .....	85
6.10 Upgraded Lagrangian Analysis.....	86
6.11 Mohr Coulomb Model and Analysis Options.....	86
6.11.1 Mohr Coulomb Model .....	86
6.11.2 Undrained Analysis with Effective Parameters .....	89
6.11.3 Undrained Analysis with Undrained Parameters .....	91
6.11.4 Relationship between Undrained Shear Strength and Soil Stiffness .....	91
6.11.5 Determination of Coefficient of Lateral Earth Pressure .....	96
6.12 PLAXIS Used in Previous Research Studies.....	98
6.13 Analysis Method of this Study.....	99
6.13.1 Selection of Field Monitored Data.....	100
6.13.2 Classification of Ground and Structural Movements.....	100
6.13.3 Empirical Method of Analysis .....	100
6.13.4 FE Analysis.....	101
6.13.4.1 Model Configuration.....	101
6.13.4.1 Simulation of Tunnel Excavation .....	102
Chapter VII .....	103
Observed and Computed Ground and Structural Movements .....	103
7.1. Ground Movements .....	103
7.1.1. Behaviors of Ground Surface and Subsurface Deformation.....	107
7.1.2. Ground Surface Settlements .....	108
7.1.3. Subsurface Settlements .....	111
7.1.4. Lateral Displacements.....	112
7.2. Structural Responses.....	114
7.3 Internal Forces of Segmental Lining.....	119
7.4. Discussion .....	128
7.4.1. Surface and Subsurface Deformation .....	128

7.4.2. Effects of Existing Structures on FE Analysis.....	129
Chapter VIII .....	130
Conclusions and Recommendations .....	130
8.1 Conclusions.....	130
8.2 Recommendations.....	131
References.....	133
Appendices.....	142
Appendix A .....	143
Summary of Soil Testing Results .....	143
Appendix B .....	150
Monitored Data .....	150
Appendix C .....	163
EPB Shield Machine .....	163
Appendix D .....	167
Model Geometries for FE Analyses and Output Graphics .....	167
Vita.....	176

## LIST OF TABLES

	Page
Table 2.1 Conventional Machines (Monsees, 1996) .....	15
Table 2.2 Special Machines (Monsees, 1996) .....	16
Table 2.3 Tunnels constructed with EPB tunneling method.....	19
Table 5.1 Types of Instrumentation and Measurements.....	69
Table 6.1 Structural properties for FEM analyses at Klongtan Bridge and BTS-Sukhumvit areas.....	95
Table 6.2 Soil parameters for FEM analyses at Klongtan Bridge area.....	95
Table 6.3 Soil parameters for FEM analyses at BTS-Sukhumvit area .....	96
Table 7.1 Magnitude of structural settlements at Klongtan Bridge area .....	119
Table A.1 Summary of test results from borehole No.8 .....	144
Table A.2 Summary of test results from borehole No.9 .....	146
Table A.3 Summary of test results from borehole No.18 .....	148
Table B.1 Data of ground surface settlement, array number GS16 .....	151
Table B.2 Data of ground surface settlement, array number GS17 .....	152
Table B.3 Data of ground surface settlement, array number GS18 .....	153
Table B.4 Data of ground surface settlement, array number GS-BTS .....	154
Table B.5 Data of ground surface settlement, array number G35 .....	154
Table B.6 Data of extensometer number ME-1 (Klongtan Bridge area).....	155
Table B.7 Data of extensometer number ME-2 (BTS-Sukumvit area) .....	155
Table B.8 Lateral movements obtained from IC (BTS-Sukumvit area).....	156
Table B.9 Lateral movements obtained from IC (cont.).....	157
Table B.10 Lateral movements obtained from IC (cont.).....	158
Table B.11 Lateral movements obtained from IC (cont.).....	159
Table B.12 Data of Klongtan bridge's settlement .....	160
Table B.13 Data of 3-storey chophouses' settlement .....	161
Table B.14 Data of 4-storey chophouses' settlement .....	162

## LIST OF FIGURES

	Page
Figure 2.1 Marc Isambard Brunel's rectangular tunneling shield (Gardner, 1996).....	7
Figure 2.2 Open TBM or gripper TBM (Wirth Company).....	9
Figure 2.3 Shielded TMB (LOVAT Company).....	10
Figure 2.4 Principle of slurry shield machine (EFNARC, 2005) .....	12
Figure 2.5 Principle of EPB shield machine (Herrenknecht Company).....	13
Figure 2.6 Applicability of soft ground machines versus grain size (Monsees, 1996).....	14
Figure 2.7 Typical EPB shield introduced by Sato Kogyo Company, 1963 (cited by Suwansawat, 2002) .....	17
Figure 2.8 Reversing belt conveyor transporting excavated soil (BMA flood diversion project, Saensaep-Latphrao Phrakanong).....	21
Figure 2.9 Train cars transporting excavated soil (BMA flood diversion project, Saensaep-Latphrao Phrakanong).....	21
Figure 2.10 Hydraulic jacks pushing on the segmental lining behind the shield (BMA flood diversion project, Saensaep-Latphrao Phrakanong).....	22
Figure 2.11 Reinforced segmental linings of BMA flood diversion project (Saensaep-Latphrao Phrakanong) .....	23
Figure 2.12 Erector arm installing a segmental lining at the crown of the tunnel (BMA flood diversion project, Saensaep-Latphrao Phrakanong).....	23
Figure 2.13 Tunnel lining after erection (BMA flood diversion project, Saensaep-Latphrao Phrakanong) .....	24
Figure 2.14 Grouting pipe attaching to grout hole (BMA flood diversion project, Saensaep-Latphrao Phrakanong).....	25
Figure 3.1 Map of Thailand (Shibuya and Tamrakar, 2003) .....	27
Figure 3.2 General subsoil profile (Teparaksa, 1999) .....	27
Figure 3.3 Piezometric level of Bangkok subsoils (Teparaksa, 1999) .....	29
Figure 3.4 Boreholes and soil profile along the route of the BMA flood diversion tunnel (Saensaep-Ladphrao Phrakanong ) .....	30

Figure 4.1 Vectors of soil displacements around model tunnel (a) in clay (Mair, 1979) and (b) in sand (Potts, 1976) (cited by O'Reilly and New, 1982).....	33
Figure 4.2 Causes of ground loss during shield tunneling.....	35
Figure 4.3 Ground movements due to shield advancement (JSCE, 1996) .....	37
Figure 4.4: Behaviors of ground displacements caused by EPB tunneling (Teparaksa, 2005a).....	38
Figure 4.5 Settlement trough above an advancing tunnel (Attewell et al., 1986).....	40
Figure 4.6 Transverse settlement trough (Peck, 1969) .....	41
Figure 4.7 Relation between settlement trough width parameter and depth of tunnel for different soil conditions (Peck, 1969) .....	42
Figure 4.8 Variation of trough width parameter, $i$ , with tunnel depth (O'Reilly and New, 1982).....	43
Figure 4.9 Shape of surface and subsurface settlement profiles (Mair et al., 1993)....	45
Figure 4.10 Variation of subsurface settlement trough width parameter, $i$ , with depth for tunnel in clays (Mair et al., 1993) .....	45
Figure 4.11 Variation of $K$ for subsurface settlement profile with depth above tunnel in clays (Mair et al., 1993) .....	46
Figure 4.12 Subsurface settlements above the tunnel axis in London Clay (Mair et al., 1993) .....	47
Figure 4.13 Correlation of maximum subsurface settlement (Luangpitakchumpol et al., 2005).....	48
Figure 4.14 Point sink (ground loss) and virtual image technique (Sagasetta, 1987)...	49
Figure 4.15 Ground loss and ovalization of a tunnel (Verruijt and Booker, 1996) .....	51
Figure 4.16 Definition $G_{AP}$ (Lee et al., 1992).....	53
Figure 5.1 Location of BMA flood diversion tunnel (Saensaep-Latphrao Phrakanong project) .....	60
Figure 5.2 Klongtan bridge area (BMA flood diversion tunnel project) .....	61
Figure 5.3 Klongtan bridge and old shophouses.....	62
Figure 5.4 BTS-Sukumvit area (BMA flood diversion tunnel project) .....	62
Figure 5.5 BTS sky train and shophouses above the curvature alignment .....	63
Figure 5.6 Subsoil profile at Klongtan Bridge area and cross section (section AA) ...	64
Figure 5.7 Subsoil profile at BTS-Sukumvit area and cross section (section BB) .....	64
Figure 5.8 General feature of articulated shield (Sramoon et al., 2006).....	65

Figure 5.9 Schematic of articulated EPB shield for MBA flood diversion tunnel (Saensaep-Latphrao Phrakanong project) .....	66
Figure 5.10 Sectional view of tunnel lining.....	67
Figure 5.11 Water sealing material (Hydrotite, RS type) .....	68
Figure 5.12 Inclinometer system (Slope Indicator Company, 2004).....	70
Figure 5.13 Incremental and cumulative deviation (Slope Indicator Company, 1994).....	71
Figure 5.14 Extensometers above and at the side of the tunnel (BMA flood diversion tunnel project) .....	72
Figure 5.15 Components of magnetic extensometer and their positions after installation (Slope Indicator Company, 2004).....	73
Figure 5.16 Total earth pressure cell and its position after embedding in the tunnel segmental lining (BMA flood diversion tunnel project) .....	74
Figure 5.17 Typical installation of convergence bolts and monitoring patterns.....	75
Figure 5.18 Tape extensometer (BMA flood diversion tunnel project).....	76
Figure 6.1 Coordinate system and sign conventions for stress components (Brinkgreve, 2002).....	79
Figure 6.2 Nodes and stress points in soil elements (Brinkgreve, 2002).....	82
Figure 6.3 Position of nodes and stress points in a 3-node and a 5-node beam element (Brinkgreve, 2002) .....	82
Figure 6.4 Results from standard drained triaxial tests (a) and Mohr Coulomb model (b) (Brinkgreve, 2002) .....	87
Figure 6.5 Mohr Coulomb yield surface in principal stress space for cohesionless soil (Brinkgreve, 2002) .....	88
Figure 6.6 Typical shear modulus and shear strains for different geotechnical works (Mair, 1993) .....	92
Figure 6.7 Variations of $G_{\text{sec(in-situ)}}/S_u$ with shear strains; (a) $S_u$ from MTX, (b) $S_u$ from field vane shear tests (Shibuya et al., 2001).....	92
Figure 6.8 Shear modulus of Bangkok clays (a) soft clay and (b) stiff clay (Teparaksa, 2005a and b).....	93
Figure 7.1 Input geometries of different analysis sections at Klongtan Bridge area; (a) GS16, (b) GS17 and (c) GS18 .....	104
Figure 7.2 Input geometries of different analysis sections at BTS-Sukhumvit area; (a) GS-BTS and (b) GS35.....	105

Figure 7.3 Finite element mesh generated at section AA (Klongtan Bridge area) ...	106
Figure 7.4 Finite element mesh generated at section BB (BTS-Sukhumvit area) .....	106
Figure 7.5 Behaviors of surface and subsurface deformation at extensometer ME-1 (Klongtan Bridge area) .....	107
Figure 7.6 Behaviors of surface and subsurface deformation at extensometer ME-2 (BTS-Sukhumvit area).....	108
Figure 7.7 Surface settlements monitored and computed at Klongtan Bridge area; (a) GS16, (b) GS17 and (c) GS18.....	109
Figure 7.8 Surface settlements monitored and computed at BTS-Sukhumvit area (a) GS-BTS and (b) GS35.....	110
Figure 7.9 Subsurface settlements along Extensometer ME-1 at Klongtan Bridge area .....	111
Figure 7.10 Subsurface settlements along Extensometer ME-2 at BTS-Sukhumvit area.....	112
Figure 7.11 Lateral displacements caused by tunnel in hard silty clay at BTS-Sukhumvit area (Inclinometer, IC).....	113
Figure 7.12 Location of structural settlement points monitored on Klongtan bridge	115
Figure 7.13 Location of point H monitored on Klongtan bridge .....	116
Figure 7.14 Behaviors of bridge foundation settlements caused by EPB tunneling in dense silty layer .....	116
Figure 7.15 Location of point C <sub>1</sub> and C <sub>2</sub> monitored on 3-storey shophouse .....	117
Figure 7.16 Behaviors of 3-storey old shophouse settlements in response to EPB tunneling in dense silty layer .....	118
Figure 7.17 Behaviors of 4-storey old shophouse settlements in response to EPB tunneling in dense silty layer .....	118
Figure 7.18 Bending moments in the tunnel lining at the final phase of simulation for section GS16, the extreme bending moment is 151.78 kNm/m.....	120
Figure 7.19 Axial forces in the tunnel lining at the final phase of simulation for section GS16, the extreme axial force is -510.18 kNm/m .....	120
Figure 7.20 Shear forces in the tunnel lining at the final phase of simulation for section GS16, the extreme shear force is 115.31 kNm/m .....	121
Figure 7.21 Axial forces in the tunnel lining at the final phase of simulation for section GS17, the extreme axial force is -505.34 kNm/m .....	122

Figure 7.22 Shear forces in the tunnel lining at the final phase of simulation for section GS17, the extreme shear force is 113.49 kNm/m .....	122
Figure 7.23 Bending moments in the tunnel lining at the final phase of simulation for section GS17, the extreme bending moment is 155.27 kNm/m.....	123
Figure 7.24 Axial forces in the tunnel lining at the final phase of simulation for section GS18, the extreme axial force is -485.61 kNm/m .....	123
Figure 7.25 Shear forces in the tunnel lining at the final phase of simulation for section GS18, the extreme shear force is 109.52 kNm/m .....	124
Figure 7.26 Bending moments in the tunnel lining at the final phase of simulation for section GS18, the extreme bending moment is 150.42 kNm/m.....	124
Figure 7.27 Axial forces in the tunnel lining at the final phase of simulation for section GS-BTS, the extreme axial force is -439.08 kNm/m.....	125
Figure 7.28 Shear forces in the tunnel lining at the final phase of simulation for section GS-BTS, the extreme shear force is 129.82 kNm/m .....	126
Figure 7.29 Bending moments in the tunnel lining at the final phase of simulation for the section GS-BTS, the extreme bending moment is -132.43 kNm/m .....	126
Figure 7.30 Axial forces in the tunnel lining at the final phase of simulation for section GS35, the extreme axial force is -370.15 kNm/m .....	127
Figure 7.31 Shear forces in the tunnel lining at the final phase of simulation for section GS35, the extreme shear force is -142.78 kNm/m .....	127
Figure 7.32 Bending moments in the tunnel lining at the final phase of simulation for section GS35, the extreme bending moment is -147.08 kNm/m .....	128
Figure A.1 Typical soil profile of borehole No.8 .....	145
Figure A.2 Engineering properties of borehole No.8 for FE analysis .....	145
Figure A.3 Typical soil profile of borehole No.9 .....	147
Figure A.4 Engineering properties of borehole No.9 for FE analysis .....	147
Figure A.5 Typical soil profile of borehole No.18 .....	149
Figure A.6 Engineering properties of borehole No.18 for FE analysis .....	149
Figure C.1 Articulated EPB shield for MBA flood diversion tunnel (Saensaep-Latphrao Phrakanong project) .....	164
Figure C.2 Front view of EPB .....	165
Figure C.3 Back view of EPB.....	165
Figure C.4 Backup unit of EPB .....	166
Figure D.1 Input geometry of section GS16.....	168

Figure D.2 Deformation mesh generated at section GS16 .....	168
Figure D.3 Total displacement arrows at section GS16 .....	168
Figure D.4 Total displacement shadings at section GS16 .....	169
Figure D.5 Input geometry of section GS17 .....	169
Figure D.6 Deformation mesh generated at section GS17 .....	169
Figure D.7 Total displacement arrows at section GS17 .....	170
Figure D.8 Total displacement shadings at section GS17 .....	170
Figure D.9 Input geometry of section GS18 .....	170
Figure D.10 Deformation mesh generated at section GS18 .....	171
Figure D.11 Total displacement arrows at section GS18 .....	171
Figure D.12 Total displacement shadings at section GS18 .....	171
Figure D.13 Input geometry of section GS-BTS .....	172
Figure D.14 Deformation mesh generated at section GS-BTS .....	172
Figure D.15 Total displacement arrows at section GS-BTS .....	172
Figure D.16 Total displacement shadings at section GS-BTS .....	173
Figure D.17 Input geometry of section GS35 .....	173
Figure D.18 Deformation mesh generated at section GS35 .....	173
Figure D.19 Total displacement arrows at section GS35 .....	174
Figure D.20 Total displacement shadings at section GS35 .....	174
Figure D.21 Input geometry of section ME-2 .....	174
Figure D.22 Deformation mesh generated at section ME-2 .....	175
Figure D.23 Total displacement arrows at section ME-2 .....	175
Figure D.24 Total displacement shadings at section ME-2 .....	175

## LIST OF SYMBOLS

2D	two dimensions or two dimensional
3D	three dimensions or three dimensional
A	sectional area, total area of settlement trough
BKK	Bangkok
BMA	Bangkok Metropolitan Administration
BTS	Bangkok Mass Transit System
<i>c</i>	cohesion
<i>c<sub>u</sub></i>	undrained cohesion
CH	inorganic clays of high plasticity
CL	inorganic clays of low to medium plasticity
Co	company
<i>D</i>	tunnel diameter
DEM	distinct element method
<i>d<sub>eq</sub></i>	equivalent thickness of a beam or plate
<i>E</i>	elastic stiffness or Young's modulus
<i>E'</i>	drained Young's modulus
<i>E<sub>50</sub></i>	average secant modulus
<i>E<sub>c</sub></i>	elastic stiffness of concrete
<i>E<sub>oed</sub></i>	oedometer modulus
<i>E<sub>sec</sub></i>	secant Young's modulus
<i>E<sub>u</sub></i>	undrained Young's modulus
<i>E<sub>ur</sub></i>	unloading Young's modulus
FDM	finite difference method
FE	finite element
FEM	finite element method
FVS	Field vane shear test
EPB	earth pressure balance
<i>g</i>	acceleration of earth gravity
<i>G</i>	shear modulus

$G_{AP}$	gap parameter
$G_p$	physical gap
$G_{sec}$	secant shear modulus
$i$	surface settlement trough width
$I$	moment inertia
IC	inclinometer
JSCE	Japan Society of Civil Engineers
JSST	Japanese standard for shield tunneling
Ltd	limited
$K$	empirical constant of proportionality or surface settlement trough width parameter, coefficient of total lateral earth pressure
$K'$	bulk modulus of soil skeleton
$K_o$	coefficient of lateral earth pressure at rest
$K_w$	bulk modulus of water
km	kilometer
m	meter
$m$	auxiliary elastic constant
ME	extensometer or magnetic extensometer
mm	millimeter
MRTA	Mass Rapid Transit Authority of Thailand
MTX	monotonic triaxial test
$n$	porosity
$N_{60}$	SPT N-value at 60% energy ratio
NATM	new Austrian tunneling method
OCR	overconsolidation ratio
OD	outer diameter
PCL	public company limited
$R$	radius of the tunnel
$r_1, r_2$	distances from the singular point and its image
$R_{inter}$	strength reduction factor of soil-structure interface
$s$	settlement
$s_{max}$	maximum settlement
$S_u$	undrained shear strength
SM-SP	poorly graded silty sand

TBM	tunnel boring machine
$u$	pore water pressure
$u^*$ <sub>3D</sub>	three-dimensional elastic deformation
$u_x$	displacement in $x$ direction
$u_y$	displacement in $y$ direction
$V_s$	volume of the surface settlement trough per unit length
$V_L$	volume loss or ground loss
$x$	transverse distance from the tunnel axis
$z$	depth from ground surface to any subsoil level
$z_0$	depth from ground surface to tunnel axis
$\alpha$	scale factor in centrifuge model testing
$\delta$	relative displacement caused by the ovalization of the tunnel, clearance between tunnel lining and tail skin of a TBM
$\Delta$	thickness of tailpiece or tail skin of a TBM
$\varepsilon$	relative uniform radial displacement of the tunnel surface or uniform radial ground loss
$\varepsilon_s$	shear train
$\gamma_c$	unit weight of concrete
$\gamma_t$	total unit weight
$\phi$	friction angle
$\phi'$	drained or effective friction angle
$\phi_u$	undrained friction angle
$\kappa$	Cam-clay swelling index
$\kappa^*$	modified swelling index
$\lambda$	proportional parameter, Cam-clay compression index
$\lambda^*$	modified compression index
$\nu$	Poisson's ratio
$\nu'$	drained Poisson's ratio
$\nu_c$	Poisson's ratio of concrete
$\nu_u$	undrained Poisson's ratio
$\rho$	bulk density
$\rho_w$	water density

$\sigma$	total stress
$\sigma'$	effective stress
$\sigma_0$	initial stress or initial overburden
$\sigma_h$	total horizontal stress
$\sigma'_h$	effective horizontal stress
$\sigma_v$	total vertical stress
$\sigma'_v$	effective vertical stress
$\omega$	workmanship factor
$\psi$	dilatancy angle