

STUDY OF TRANSISTOR PARAMETERS
TO
UTILIZE IN COMPANDOR CIRCUIT



by
SUSAK THONGTHANLACHAT

307026

A thesis submitted in partial fulfillment
of the requirements for the Degree of
Master of Engineering

Department of Electrical Engineering
The Faculty of the Graduate School
Chulalongkorn University

February, 1964.

Accepted by the Graduate School, Chulalongkorn University, in partial fulfillment of the requirements for the Degree of Master of Engineering.

T. Nilarnidhi

.....

Dean of the Graduate School

Thesis Committee

..... Suvain Sangpetch

Chairman

..... B. Phienpani

..... Aporn Kung

Thesis Supervisor

..... B. Phienpani

..... Aporn Kung

Date March 23, 1964

PREFACE



The compandor circuit was firstly come across the author by introduction of Mr. Boonhoo Phienpanij, Engineer in Charge of the Provincial telephone and Long line Division, and from an article in the Post Office Electrical Engineer's Journal. At that time, the author had a very small background in transistor theory. There upon, a lot of painstaking works had been devoted in order to obtain the required knowledge in both theory and practices of transistorized circuit. From practical point of view, the compandor is very helpful for long distance telephone circuit but an expensive one too. The author then began to construct a transistorized compandor by himself upon the purposes of securing more understanding in its characteristics and trying to use it in the existing telephone system. However, many problems have occurred during conducting the experiments as the reader will find in Chapter III. Eventually, the work has been completed.

The author wishes to express his gratitude and appreciation to Mr. Boonhoo Phienpanij whose suggestion led to the undertaking of the problems and under whose guidance the experimentation was completed; and also to Mr. Sawart Srikham; Mr. Term Budhi-pinyo; Mr. Pleumjai Sinarkorn, Mr. Banleng Mukdapa-korn which helped to make this work possible.

CONTENTS

| | Page |
|-----------------------------------------|----------|
| Preface | i |
| List of figures | iv |
| CHAPTER | |
| I INTRODUCTION | 1 |
| Introduction to Compandors | 1 |
| Advantage of Transistor Compandor | 2 |
| The purpose of Thesis | 2 |
| II THEORY OF COMPANDOR | 3 |
| Basic Principles | 3 |
| Basic Circuits of Compandor | 4 |
| Compressor Variable Loss Device | 6 |
| Expander Variable Loss Device | 15 |
| Control Current Rectifier | 18 |
| Amplifier | 20 |
| Compandor | 32 |
| Noise Reduction | 34 |

| | Page |
|---------------------------------------|------|
| CHAPTER | |
| III EXPERIMENTAL WORK | |
| Introduction | 39 |
| Compressor Variable Loss Device | 40 |
| Expander Variable Loss Device | 47 |
| Control Current Rectifier | 49 |
| Amplifier | 66 |
| Compressor | 68 |
| Expander | 73 |
| IV CONCLUSION | 79 |
| BIBLIOGRAPHY | 82 |

v
iv

LIST OF FIGURES

| FIGURE | Page |
|----------------------------------------------------------------------------------|------|
| 1. Ideal steady state characteristic of compander. | 4 |
| 2. Basic circuit of compressor. | 5 |
| 3. Basic circuit of expander. | 6 |
| 4. Four terminal active network. | 8 |
| 5. Variable loss as shunt element. | 9 |
| 6. Variation of α with emitter current and collector voltage. | 10 |
| 7. Variation of collector resistance with emitter current and collector voltage. | 10 |
| 8. Variation of r_m with emitter current and collector voltage. | 11 |
| 9. Variation of $r_c (1 - \alpha)$ with emitter current and collector voltage. | 11 |
| 10. Variation of emitter resistance with emitter current and collector voltage. | 12 |
| 11. Variation of base resistance with emitter current and collector voltage. | 12 |
| 12. Compressor variable loss device | 15 |
| 13. Expander variable loss device | 17 |
| 14. A.C. input resistance/ control current characteristic. | 18 |

| FIGURE | Page |
|----------------------------------------------------------------|------|
| 15. Rectifier regarded as four-terminal network | 18 |
| 16. Control current rectifier | 19 |
| 17. Corresponding configurations of transistor and vacuum tube | 20 |
| 18. Current and voltage amplification | 23 |
| 19. Multistage amplifier | 24 |
| 20. Three-stage amplifier | 26 |
| 21. Simplified coupling network | 27 |
| 22. Shunt feedback | 29 |
| 23. $A^{\circ}\beta$ diagram for the circuit of Fig.22 | 30 |
| 24. Series feedback | 30 |
| 25. Multistage series feedback | 31 |
| 26. Multistage shunt feedback | 32 |
| 27. Circuit diagram of compressor | 33 |
| 28. Circuit diagram of expander | 35 |
| 29. Level diagram for a carrier system containing a compander | 36 |
| 30. Compander response to discrete signals | 37 |
| 31. Compressor variable loss device | 40 |
| 32. A.C.resistance/control current characteristic, DATA NO3 | 43 |
| 33. A.C. resistance/control current characteristic, DATA NO2 | 44 |
| 34. A.C.resistance/control current characteristic, DATA NO 3 | 45 |
| 35. A.C.resistance/control current characteristic, DATA NO4 | 46 |

| FIGURE | Page |
|--------------------------------------------------------------|------|
| 36. Expander variable loss device | 47 |
| 37. A.C.resistance/control current characteristic, DATA NO 5 | 48 |
| 38. Control current rectifier | 49 |
| 39. Input-level/control-current characteristic, DATA NO 6, | |
| 14. | 58 |
| 40. Input-level/control-current characteristic, DATA NO 10, | |
| 18. | 59 |
| 41. Input-level/control current characteristic, DATA NO 8, | |
| 15 | 60 |
| 42. Input-level/control current characteristic, DATA NO 11, | |
| 19. | 61 |
| 43 Input-level/control current characteristic, DATA NO 7, | |
| 16. | 62 |
| 44. Input- level/control current characteristic, DATA NO 12 | |
| 20 | 63 |
| 45. Input-level/control current characteristic, DATA NO 9 | |
| 17. | 64 |
| 46. Input-level/control current characteristic, DATA NO 13, | |
| 21. | 65 |
| 47. High gain amplifier using with compressor | 66 |

| FIGURE | Page |
|--------------------------------------------------------------|------|
| 48. Pre-amplifier using with expander | 67 |
| 49. Amplifier using with expander | 67 |
| 50. Input/output characteristic of compressor, DATA NO 22 | 70 |
| 50A. GAIN/INPUT characteristic of compressor. | 72 |
| 51. Input/output characteristic of expander, DATA NO 23 | 75 |
| 51A. GAIN/INPUT characteristic of expander, DATA NO 23A | 77 |
| 52. Compressor | 78 |
| 53. Expander | 78 |